

Section 1: Identification

Product identifier

Product Name • **Stainless Steel, All Grades**

Chemical Name • No data available

Product Description • Solid material in the form of round and shaped wires, bars, and rope. This SDS applies to all grades of stainless steel produced by Central Wire.

Relevant identified uses of the substance or mixture and uses advised against

Recommended use • No data available

Details of the supplier of the safety data sheet

Manufacturer • Central Wire Industries Ltd.
1 North Street
Perth, Ontario K7H 2S2 Canada
<http://www.centralwire.com>

Manufacturing Locations

US Locations: Dumas, AR; Fond du Lac, WI; Houston, TX; Michigan City, IN; Milton, FL; Naples, FL; Perris, CA; Pomfret, CT; Union, IL

Canada Locations: Perth, ON; Calgary, AB

United Kingdom Location: Rotherham, South Yorkshire, England

Emergency telephone number

Manufacturer • 613-326-3006

Section 2: Hazard Identification

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

OSHA HCS 2012 • This product is generally an article* and is considered non-hazardous in its solid form, but is regulated under OSHA for the release of dust and fumes during mechanical processing operations.

Skin Irritation 2

Eye Irritation 2

Skin Sensitization 1B

Carcinogenicity 1B

Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation

Specific Target Organ Toxicity Single Exposure 1

Specific Target Organ Toxicity Repeated Exposure 1

Combustible Dust

Respiratory Sensitization 1B

*"Article" means a manufactured item: (i) which is formed to a specific shape or design during manufacture; (ii) which has end use function(s) dependent in whole or in part upon its shape or design during end use; and (iii) which does not release, or otherwise result in exposure to, a hazardous chemical under normal conditions of use.

Label elements

OSHA HCS 2012

DANGER



- Hazard statements**
- There are no health hazards from stainless steel wire in solid form. Exposure to dust and/or fumes from processing such as burning, welding, sawing, brazing and grinding may cause serious health effects.
 - Causes skin irritation.
 - May cause an allergic skin reaction.
 - Causes serious eye irritation.
 - May cause respiratory irritation.
 - Suspected of causing cancer.
 - Causes damage to organs - lungs via inhalation.
 - Causes damage to organs - lungs through prolonged or repeated exposure via inhalation.
 - May form combustible dust concentrations in air.

Precautionary statements

- Prevention**
- Obtain special instructions before use.
 - Do not handle until all safety precautions have been read and understood.
 - Avoid breathing dusts, fumes and gasses.
 - Wash thoroughly after handling.
 - Do not eat, drink or smoke when using this product.
 - Contaminated work clothing should not be allowed out of the workplace.
 - Wear protective gloves - work gloves and eye/face protection - safety glasses or goggles.
 - In case of inadequate ventilation wear respiratory protection.
- Response**
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF exposed or concerned: Get medical advice/attention.
 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
 - IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
- Storage/Disposal**
- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.
 - Refer to manufacturer/supplier for information on recovery/recycling.

Other hazards

OSHA HCS 2012

- No data available

Other information

NFPA •Health = 1, Flammability = 0, Special Information = None

HMIS •Health = 1*, Flammability = 0, Reactivity = 0, PPE = E

* Chronic Health Hazard

E = Safety glasses, gloves and respirator if above exposure levels

Section 3 - Composition/Information on Ingredients

Mixtures

Stainless steel in its solid state is not considered hazardous. However, operations such as burning, welding, sawing, brazing or grinding may release dust and/or fumes, which may present health hazards. These elements may appear in some or various combinations in any particular grade of stainless steel.

| Composition | | | |
|---------------|----------------|--------|-----------|
| Chemical Name | Identifiers | % | Hazardous |
| Aluminum | CAS: 7429-90-5 | < 3.5% | Yes |
| Chromium | CAS: 7440-47-3 | < 30% | Yes |
| Cobalt | CAS: 7440-48-4 | < 30% | Yes |
| Copper | CAS: 7440-50-8 | < 34% | Yes |
| Iron | CAS: 7439-89-6 | < 85% | No |
| Manganese | CAS: 7439-96-5 | < 10% | Yes |
| Molybdenum | CAS: 7439-98-7 | < 18% | No |
| Nickel | CAS: 7440-02-0 | < 35% | Yes |
| Silicon | CAS: 7440-21-3 | < 4.5% | Yes |
| Tantalum | CAS: 7440-25-7 | < 5.5% | Yes |
| Tungsten | CAS: 7440-33-7 | < 6.5% | Yes |
| Vanadium | CAS: 7440-62-2 | < 0.5% | Yes |

Non-Metallic Coatings - Other Information

Dry lube and oil based wire coatings • Individual wire coating components are present at values below the reporting requirements of GHS concentration limits.

Section 4: First-Aid Measures

Description of first aid measures

Inhalation • IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.

Skin • If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Eye • IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion • Low hazard for usual industrial or commercial handling. Get medical attention if symptoms occur.

Most important symptoms and effects, both acute and delayed

- Refer to Section 11 - Toxicological Information.

Section 5: Fire-Fighting Measures

Extinguishing media

Suitable Extinguishing Media • For solid formed alloys, as appropriate for surrounding fire. A fire involving finely divided alloy should be treated as a Class D metal fire. Use DRY sand, graphite powder, dry sodium chloride based extinguishers, G-1 or Met-L-X powder.

Unsuitable Extinguishing Media • Do not use halogenated extinguishing agents or foam.

Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards

- Stainless steel products in the form shipped are not considered combustible. During subsequent processing (cutting, welding, grinding, etc.), the generation of dust in high concentrations may present fire and explosion hazards.

Hazardous Combustion Products

- May produce hazardous metal fumes.

Advice for firefighters

- Fire fighters should wear complete protective clothing including self-contained breathing apparatus.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal Precautions • No data available

Emergency Procedures • Solid Form: Not Applicable. In dusty environment, ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Clean up using methods which avoid dust generation. Compressed air should not be used. During cleanup avoid inhalation and skin and eye contact. Provide local exhaust or dilution ventilation as required.

Environmental precautions

- No data available.

Methods and material for containment and cleaning up

Containment/Clean-up Measures • Use appropriate Personal Protective Equipment (PPE)
Use clean non-sparking tools to collect material and place it into loosely covered plastic containers for later disposal.
Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).

Section 7 - Handling and Storage

Precautions for safe handling

Handling • No specific requirements for solid formed steel product. Do not breathe (dust or fumes). Do not use in areas without adequate ventilation. Do not use sparking tools. Keep away from heat and ignition sources – No Smoking. Use good safety and industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Storage • Do not store and transport with oxidizers, acids, etc.

Special Packaging Materials • None for solid stainless steel product.

Incompatible Materials or Ignition Sources • Oxidizers. Reacts with strong acids to form explosive hydrogen gas and oxides of nitrogen.

Section 8 - Exposure Controls/Personal Protection

Control parameters

Exposure Limits/Guidelines • No data available on product. Individual elements may be emitted during processing.

| Exposure Limits/Guidelines | | | | |
|-------------------------------------|--------|--|--|--|
| | Result | ACGIH | NIOSH | OSHA |
| Vanadium (7440-62-2) | TWAs | Not established | 1 mg/m ³ TWA (listed under Ferrovandium dust) | Not established |
| Aluminum (7429-90-5) | TWAs | 1 mg/m ³ TWA (respirable fraction) | 10 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable dust) | 15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction) |
| Silicon (7440-21-3) | TWAs | Not established | 10 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable dust) | 15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction) |
| Tantalum (7440-25-7) | TWAs | Not established | 5 mg/m ³ TWA (dust) | 5 mg/m ³ TWA |
| Exposure Limits/Guidelines (cont'd) | | | | |
| Tungsten (7440-33-7) | TWAs | 5 mg/m ³ TWA | 5 mg/m ³ TWA | Not established |
| Manganese (7439-96-5) | TWAs | 0.02 mg/m ³ TWA (respirable fraction); 0.1 mg/m ³ TWA (inhalable fraction) | 1 mg/m ³ TWA (fume) | Not established |
| Molybdenum (7439-98-7) | TWAs | 10 mg/m ³ TWA (inhalable fraction); 3 mg/m ³ TWA (respirable fraction) | Not established | Not established |
| Chromium (7440-47-3) | TWAs | 0.5 mg/m ³ TWA | 0.5 mg/m ³ TWA | 1 mg/m ³ TWA |
| Cobalt (7440-48-4) | TWAs | 0.02 mg/m ³ TWA | 0.05 mg/m ³ TWA (dust and fume) | 0.1 mg/m ³ TWA (dust and fume) |
| Nickel (7440-02-0) | TWAs | 1.5 mg/m ³ TWA (inhalable fraction) | 0.015 mg/m ³ TWA | 1 mg/m ³ TWA |

Exposure controls

Engineering

Measures/Controls

- Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Use only appropriately classified electrical equipment.

Personal Protective Equipment

Pictograms



Respiratory

- Use of a NIOSH/MSHA approved dust respirator is recommended where airborne dust levels exceed appropriate PELs and TLVs.

Eye/Face

- Wear protective eyewear (goggles, face shield, or safety glasses).

Hands

- Wear protective gloves - suitable for protection against physical injury and skin contact during handling and processing.

Skin/Body

- Wear protective clothing - such as long sleeves and or coveralls during processing.

General Industrial

Hygiene Considerations

- Practice good housekeeping and avoid creating/breathing dust. Do not allow dust to collect. Maintain, clean, and fit test respirators in accordance with OSHA regulations. Provide readily accessible eyewash stations.

Environmental Exposure Controls

- No data available

Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

| Material Description | | | |
|--|----------------------|-------------------------------------|---|
| Physical Form | Solid | Appearance/Description | Solid wire of various grades. |
| Color | Silver-gray metallic | Odor | Odorless |
| Taste | No data available. | Particulate Type | No data available |
| Particulate Size | No data available | Aerosol Type | No data available |
| Odor Threshold | No data available | Physical and Chemical Properties | No data available |
| General Properties | | | |
| Boiling Point | No data available | Melting Point | 2500 to 2800 F(1371 to 1538 C) |
| Decomposition Temperature | No data available | Heat of Decomposition | No data available |
| pH | No data available | Specific Gravity/Relative Density | No data available |
| Density | No data available | Bulk Density | 7.75 g/cm ³ 0.28 lb/in ³ |
| Water Solubility | Insoluble | Solvent Solubility | No data available |
| Viscosity | No data available | Explosive Properties | No data available |
| Oxidizing Properties: | No data available | | |
| Volatility | | | |
| Vapor Pressure | No data available | Vapor Density | No data available |
| Evaporation Rate | No data available | VOC (Wt.) | No data available |
| VOC (Vol.) | No data available | Volatiles (Wt.) | No data available |
| Volatiles (Vol.) | No data available | | |
| Flammability | | | |
| Flash Point | No data available | UEL | No data available |
| LEL | No data available | Autoignition | No data available |
| Self-Accelerating Decomposition Temperature (SADT) | No data available | Heat of Combustion (ΔH_c) | No data available |
| Burning Time | No data available | Flame Height | No data available |
| Flame Extension | No data available | Ignition Distance | No data available |
| Flame Duration | No data available | Flammability (solid, gas) | Not Applicable. |
| Environmental | | | |
| Half-Life | No data available | Octanol/Water Partition coefficient | No data available |
| Coefficient of water/oil distribution | No data available | Bioaccumulation Factor | No data available |
| Bioconcentration Factor | No data available | Biochemical Oxygen Demand BOD/BOD5 | No data available |
| Chemical Oxygen Demand | No data available | Persistence | No data available |
| Degradation | No data available | | |

Section 10: Stability and Reactivity

Reactivity

- No dangerous reaction known under conditions of normal use.

Chemical stability

- Stable

Possibility of hazardous reactions

- Hazardous polymerization will not occur.

Conditions to avoid

- Incompatible materials.

Incompatible materials

- Incompatible Materials: oxidizers, strong acids

Hazardous decomposition products

- Hazardous decomposition may occur during certain operations such as welding, burning, melting or hot rolling, generating hazardous metal fumes. Hexavalent chromium which is a suspect carcinogen may result from pickling of stainless steel.

Section 11 - Toxicological Information

Information on toxicological effects

- Other Material Information**
- Toxicological impacts expected to be minimal for products in purchased form. Individual component information is provided below if available.

| | | Components |
|---------------------------|-----------|--|
| Aluminum (< 3.5%) | 7429-90-5 | Multi-dose Toxicity: Inhalation-Rat TLo • 206 mg/m ³ 5 Hour(s) 30 Day(s)-Intermittent; <i>Lungs, Thorax, or Respiration:</i> Fibrosis (interstitial); Endocrine: Hypoglycemia; <i>Blood:</i> Changes in serum composition (e.g., TP, bilirubin cholesterol) |
| Chromium (< 30%) | 7440-47-3 | Tumorigen / Carcinogen: Implant-Rat TLo • 1200 µg/kg 6 Week(s)-Intermittent; <i>Tumorigenic:</i> Equivocal tumorigenic agent by RTECS criteria; Blood: Lymphoma, including Hodgkin's disease; <i>Tumorigenic:</i> Tumors at site of application; Intravenous-Rat TLo • 2160 µg/kg 6 Week(s)-Intermittent; <i>Tumorigenic:</i> Equivocal tumorigenic agent by RTECS criteria; Gastrointestinal: Tumors; <i>Blood:</i> Lymphoma, including Hodgkin's disease |
| Copper (< 34%) | 7440-50-8 | Acute Toxicity: Ingestion/Oral-Mouse LD50 • 413 mg/kg; Ingestion/Oral-Human TLo • 120 µg/kg; <i>Gastrointestinal:</i> Nausea or vomiting |
| Manganese (< 10%) | 7439-96-5 | Irritation: Eye-Rabbit • 500 mg 24 Hour(s) • Mild irritation; Skin-Rabbit • 500 mg 24 Hour(s) • Mild irritation; Multi-dose Toxicity: Inhalation-Rat TLo • 3709 mg/m ³ 6 Hour(s) 13 Week(s)-Intermittent; <i>Brain and Coverings:</i> Other degenerative changes; Behavioral: Changes in motor activity (specific assay); <i>Lungs, Thorax, or Respiration:</i> Other changes; Inhalation-Rat TLo • 0.3 mg/m ³ 5 Hour(s) 26 Week(s)-Intermittent; <i>Lungs, Thorax, or Respiration:</i> Fibrosis (interstitial); Immunological Including Allergic: Decrease in cellular immune response |
| Molybdenum (< 18%) | 7439-98-7 | Multi-dose Toxicity: Ingestion/Oral-Rat TLo • 7 mg/kg 2 Week(s)-Intermittent; <i>Liver:</i> Other changes; <i>Biochemical:</i> Enzyme inhibition, induction, or change in blood or tissue levels: Other oxidoreductases |
| Nickel (< 80%) | 7440-02-0 | Acute Toxicity: Ingestion/Oral-Rat LDLo • 500 mg/kg; <i>Gastrointestinal:</i> Other changes; Inhalation-Mouse TLo • 10 mg/m ³ 2 Hour(s); <i>Immunological Including Allergic:</i> Decrease in cellular immune response; Multi-dose Toxicity: Inhalation-Rabbit TLo • 130 µg/m ³ 6 Hour(s) 35 Week(s)-Intermittent; <i>Lungs, Thorax, or Respiration:</i> Other changes; <i>Biochemical:</i> Metabolism (intermediary): Lipids, including transport; Inhalation-Rat TLo • 350 mg/m ³ 2 Week(s)-Intermittent; <i>Lungs, Thorax, or Respiration:</i> Other changes; <i>Blood:</i> Changes in erythrocyte (RBC) count; <i>Related to Chronic Data:</i> Death in the Other Multiple Dose data type field; Tumorigen / Carcinogen: Inhalation-Guinea Pig TLo • 15 mg/m ³ 91 Week(s)-Intermittent; <i>Tumorigenic:</i> Equivocal tumorigenic agent by RTECS criteria; Lungs, Thorax, or Respiration: Tumors; <i>Lungs, Thorax, or Respiration:</i> Bronchiogenic carcinoma; Intramuscular-Rat TLo • 56 mg/kg; <i>Tumorigenic:</i> Carcinogenic by RTECS criteria; Musculoskeletal: Tumors; <i>Tumorigenic:</i> Tumors at site of application; Subcutaneous-Rat TLo • 3000 mg/kg 6 Week(s)-Intermittent; <i>Tumorigenic:</i> Equivocal tumorigenic agent by RTECS criteria; Skin and Appendages: Other:Tumors; <i>Tumorigenic:</i> Tumors at site of application |
| Silicon (< 4.5%) | 7440-21-3 | Acute Toxicity: Ingestion/Oral-Rat LD50 • 3160 mg/kg; Irritation: Eye-Rabbit • 3 mg • Mild irritation |
| Tantalum (< 5.5%) | 7440-25-7 | Acute Toxicity: Ingestion/Oral-Mouse LD50 • 595 mg/kg |
| Tungsten (< 6.5%) | 7440-33-7 | Irritation: Eye-Rabbit • 500 mg 24 Hour(s) • Mild irritation; Skin-Rabbit • 500 mg 24 Hour(s) • Mild irritation |
| GHS Properties | | Classification |
| Acute toxicity | | OSHA HCS 2012•Acute Toxicity - Dermal - Not relevant; Acute Toxicity - Inhalation - No data available; Acute Toxicity - Oral - Not relevant |
| Aspiration Hazard | | OSHA HCS 2012•Data lacking |
| Carcinogenicity | | OSHA HCS 2012•Carcinogenicity 1B |
| Germ Cell Mutagenicity | | OSHA HCS 2012•No data available |
| Skin corrosion/Irritation | | OSHA HCS 2012•Skin Irritation 2 |
| Skin sensitization | | OSHA HCS 2012•Skin Sensitizer 1B |

| | |
|-------------------------------|--|
| STOT-RE | OSHA HCS 2012•Specific Target Organ Toxicity Repeated Exposure 1 |
| STOT-SE | OSHA HCS 2012•Specific Target Organ Toxicity Single Exposure 1; Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation |
| Toxicity for Reproduction | OSHA HCS 2012•Data lacking |
| Respiratory sensitization | OSHA HCS 2012•Respiratory Sensitizer 1B |
| Serious eye damage/Irritation | OSHA HCS 2012•Eye Irritation 2 |

- Target Organs**
- Skin/Dermal, Lungs, Central Nervous System (CNS), Liver/Hepatotoxin, Kidney/Nephrotoxin, Metal Fume Fever, Nasal Cavity
- Route(s) of entry/exposure**
- Dermal contact with and/or inhalation of dust or fumes during welding, cutting, grinding, burning, and other operations. Overexposure to dusts and/or fume generated during processing can pose health hazards as defined below:
- Medical Conditions Aggravated by Exposure**
- May aggravate asthma or other respiratory disorders. May aggravate skin disorders.

Potential Health Effects

Inhalation

- Acute (Immediate)**
- May cause respiratory irritation. May cause sensitization. May cause metal fume fever.
- Chronic (Delayed)**
- Prolonged inhalation of dust or fume may cause lung, central nervous system, liver, kidney and nasal cavity damage.

Skin

- Acute (Immediate)**
- Causes skin irritation. May cause skin sensitization. Symptoms include redness, and skin rash.
- Chronic (Delayed)**
- Repeated and prolonged exposure may cause irritation. Repeated and prolonged exposure may cause sensitization.

Eye

- Acute (Immediate)**
- Exposure to dust and fumes may cause irritation. Exposure to fumes and dusts may cause sensitization and conjunctivitis.
- Chronic (Delayed)**
- Repeated and prolonged exposure to dust and fumes may cause irritation. Repeated and prolonged exposure to dusts and fumes may cause sensitization and conjunctivitis.

Ingestion

- Acute (Immediate)**
- Low hazard for usual industrial or commercial handling. Gastrointestinal disturbances including nausea and vomiting may result from ingestion of dusts.
- Chronic (Delayed)**
- Low hazard for usual industrial or commercial handling. Repeated and prolonged exposure may cause gastrointestinal disturbances including nausea and vomiting.

- Carcinogenic Effects**
- No carcinogenic effects resulting from exposure to stainless steels have been reported, either in epidemiological studies or in tests with animals. Stainless steel does contain carcinogenic components above the cut-off threshold amount of 0.1% (nickel and cobalt) and therefore stainless steel (as dusts and fumes) must be classified as a carcinogen.

| Carcinogenic Effects | | | |
|----------------------------|-----------|------------------------------|---|
| | CAS | IARC | NTP |
| Chromium | 7440-47-3 | Group 3-Not Classifiable | Not Listed |
| Cobalt | 7440-48-4 | Group 2B-Possible Carcinogen | Not Listed |
| Nickel | 7440-02-0 | Group 2B-Possible Carcinogen | Reasonably Anticipated to be Human Carcinogen |
| Nickel as Nickel Compounds | NDA | Group 1-Carcinogenic | Known Human Carcinogen |

Section 12 - Ecological Information

Toxicity

- No information available at this time. As with all foreign substances do not allow to enter the storm drainage systems.

Persistence and degradability

- No data available

Bioaccumulative potential

- No data available

Mobility in Soil

- No data available

Section 13 - Disposal Considerations

Waste treatment methods

- Product waste** • Product as shipped is not considered hazardous and should be recycled. Product dusts from processing may be classified as hazardous waste, as defined in 40 CFR 261 as well as state and/or local regulation. Solid waste generated from product processing should be classified by a competent environmental professional and disposed, processed or recycled in accordance with federal, state and local regulation.
- Packaging waste** • Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

| | UN number | UN proper shipping name | Transport hazard class(es) | Packing group | Environmental hazards |
|----------|-----------|-------------------------|----------------------------|---------------|-----------------------|
| DOT | NDA | NDA | NDA | NDA | NDA |
| TDG | NDA | NDA | NDA | NDA | NDA |
| IMO/IMDG | NDA | NDA | NDA | NDA | NDA |

Special precautions for user

- No special precautions.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

- Not Applicable.

Other information

DOT • Not regulated as a hazardous material.

TDG • Not regulated as a dangerous good.

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • Acute, Chronic. SARA Hazard Classifications pertain to product as dust and fume.

| Inventory | | | |
|------------|-----------|------------|------|
| Component | CAS | Canada DSL | TSCA |
| Aluminum | 7429-90-5 | Yes | Yes |
| Chromium | 7440-47-3 | Yes | Yes |
| Cobalt | 7440-48-4 | Yes | Yes |
| Copper | 7440-50-8 | Yes | Yes |
| Iron | 7439-89-6 | Yes | Yes |
| Manganese | 7439-96-5 | Yes | Yes |
| Molybdenum | 7439-98-7 | Yes | Yes |
| Nickel | 7440-02-0 | Yes | Yes |
| Silicon | 7440-21-3 | Yes | Yes |
| Tantalum | 7440-25-7 | Yes | Yes |
| Tungsten | 7440-33-7 | Yes | Yes |
| Vanadium | 7440-62-2 | Yes | Yes |

Canada

Labor

Canada - WHMIS - Classifications of Substances

| | | |
|---|-----------|--|
| •Stainless Steel Wire and ingredients (unless listed below) | | Not Listed |
| •Copper | 7440-50-8 | Uncontrolled product according to WHMIS classification criteria |
| •Chromium | 7440-47-3 | Uncontrolled product according to WHMIS classification criteria |
| •Manganese | 7439-96-5 | D2A (including powder) |
| •Tantalum | 7440-25-7 | Uncontrolled product according to WHMIS classification criteria |
| •Cobalt | 7440-48-4 | D2A, D2B |
| •Aluminum | 7429-90-5 | B6 (powder); Uncontrolled product according to WHMIS classification criteria |
| •Molybdenum | 7439-98-7 | Uncontrolled product according to WHMIS classification criteria |
| •Nickel | 7440-02-0 | D2A, D2B; B6, D2A (Raney) |
| •Silicon | 7440-21-3 | B4 |
| •Tungsten | 7440-33-7 | Uncontrolled product according to WHMIS classification criteria |
| •Vanadium | 7440-62-2 | Not Listed |
| •Iron | 7439-89-6 | Uncontrolled product according to WHMIS classification criteria |

Canada - WHMIS - Ingredient Disclosure List

| | | |
|---|-----------|------------|
| •Stainless Steel Wire and ingredients (unless listed below) | | Not Listed |
| •Copper | 7440-50-8 | 1 % |
| •Chromium | 7440-47-3 | 0.1 % |
| •Manganese | 7439-96-5 | 1 % |
| •Tantalum | 7440-25-7 | 1 % |
| •Cobalt | 7440-48-4 | 0.1 % |
| •Aluminum | 7429-90-5 | 1 % |
| •Molybdenum | 7439-98-7 | 1 % |
| •Nickel | 7440-02-0 | 0.1 % |
| •Tungsten | 7440-33-7 | 1 % |
| •Vanadium | 7440-62-2 | 1 % |

United States

Environment

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

•Stainless Steel Wire and ingredients (unless listed below)

Not Listed

5000 lb final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100 µm); 2270 kg final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100 µm)

•Copper

7440-50-8

5000 lb final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100 µm); 2270 kg final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100 µm)

•Chromium

7440-47-3

100 lb final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100 µm); 45.4 kg final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100 µm)

•Nickel

7440-02-0

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs

•Stainless Steel Wire and ingredients (unless listed below)

Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs

•Stainless Steel Wire and ingredients (unless listed below)

Not Listed

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

•Stainless Steel Wire and ingredients (unless listed below)

Not Listed

•Copper

7440-50-8

1.0 % de minimis concentration

•Chromium

7440-47-3

1.0 % de minimis concentration

•Manganese

7439-96-5

1.0 % de minimis concentration

•Cobalt

7440-48-4

0.1 % de minimis concentration

•Aluminum

7429-90-5

1.0 % de minimis concentration (dust or fume only)

•Nickel

7440-02-0

0.1 % de minimis concentration

•Vanadium

7440-62-2

1.0 % de minimis concentration (except when contained in an alloy)

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List

•Stainless Steel Wire and ingredients (unless listed below)

Not Listed

•Cobalt

7440-48-4

carcinogen, initial date 7/1/92 (powder)

•Nickel

7440-02-0

carcinogen, initial date 10/1/89 (metallic)

Section 16 - Other Information

| | |
|---|---|
| Classification method for mixtures | <ul style="list-style-type: none">• Cut-off values/concentration limits of ingredients. |
| Last Revision Date | <ul style="list-style-type: none">• January 21, 2021 |
| Preparation Date | <ul style="list-style-type: none">• June 8, 2015 |
| Review Date | <ul style="list-style-type: none">• January 2, 2024 |
| Disclaimer/Statement of Liability | <ul style="list-style-type: none">• This information is taken from sources or based upon data believed to be reliable. However, Central Wire Industries Ltd makes no warranty as to the absolute correctness or sufficiency of any of the foregoing information or that additional or other measures may not be required under particular conditions. |
